

Yealink

W70B



HIGH-PERFORMANCE DECT IP PHONE SYSTEM WITH USER-CENTRIC DESIGN

The Yealink® DECT IP phone W70B cordless phone system is the ideal solution for small and medium-sized businesses. It empowers users with the convenience of wireless communication along with the feature richness of VoIP telephony. Pairing with up to a total of 10 Yealink W52H/ W56H DECT handsets, the W70B provides superb mobility and flexibility.

- High-performance SIP cordless phone system
- 2.4" 240 x 320 color screen with intuitive user interface
- 20 simultaneous calls
- Up to 10 DECT cordless handsets per base
- Up to 30 hours of talk time
- Up to 400 hours of standby time
- Up to 10 SIP accounts
- Quick charging: 10-min charge time for 2-hour talk time
- TLS and SRTP security encryption
- Noise Reduction System
- Headset connection via 3.5 mm jack
- Charger wall mountable

W70B PHONE PRODUCT SPECIFICATIONS

Phone Features

- Up to 20 simultaneous calls
- Up to 10 handsets
- Up to 10 SIP accounts
- Up to 6 repeaters per base station (RT30)
- No Perception Upgrade
- Paging/Intercom/Auto answer/Dial plan
- Call hold/Call transfer/Call waiting
- 3-way conference
- Switching between calls
- Mute/Silence/DND
- Caller ID with name and number
- Anonymous call/Anonymous call rejection
- Call forward: Always/Busy/No Answer
- Speed dial/Voicemail/Redial
- Message Waiting Indication (MWI)
- Music on hold (server-based)
- Local phonebook for up to 1000 entries (store in the base)
- Remote phonebook/LDAP/XML phonebook
- Phonebook search/import/export
- Call history: All/Missed/Placed/Received
- Reset to factory, reboot
- Emergency call
- Shared Call Appearance (SCA)
- Action URI
- XML browser

Personalization

- 9 ringer melodies
- Screen saver
- Multilingual user interface

Management

- Auto-provision via TFTP/FTP/HTTP/HTTPS/RPS
- Auto-provision with PnP
- Handset upgrade: OTA (Over-The-Air)/No Perception

Audio Features

- Full-duplex speakerphone
- Hearing Aid Compatibility (HAC) compliant
- Receiver volume control: 5 steps
- Acoustic warning for low battery status

- Wideband codec: G.722
- DTMF
- Ringer volume control: 5 steps+off
- Multiple advisory tones
- Narrowband codec: PCMU, G.729
- VAD, CNG, AGC, PLC, AJB
- AEC (supported by W52H and W56H)
- Support VQ-RTCPXR (RFC6035)

Network features

- SIP v1 (RFC2543), v2 (RFC3261)
- SNTP/NTP
- VLAN (802.1Q and 802.1P)
- 802.1x, LLDP, PPPoE
- STUN Client (NAT Traversal)
- UDP/TCP/TLS
- IP assignment: static/DHCP
- Support outbound proxy server backup Security
- Open VPN
- HTTPS (server/client)
- Digest authentication using MD5
- Secure configuration file via AES encryption
- Support SHA256/SHA512/SHA384
- Three-level configuration mode: Admin/Var/User

DECT

- Frequency bands: 1880 – 1900 MHz (Europe), 1920 – 1930 MHz (US)
- DECT Standards: CAT-iq2.0

Interface

- 1 x RJ45 10/100M Ethernet port
- Power over Ethernet (IEEE 802.3af), Class 1
- Headset jack (3.5 mm)

Physical Features

- Indoor Range: 20m~50m (The ideal distance is 50m)
- Outdoor Range: 300m (in ideal conditions)
- Standby Time: 400 hours (in ideal conditions)
- Talk Time: 30 hours
- 2.4" 240x320 pixels color display

- Desktop or wall mountable
- Three LED indicators on W70B:
 - 1 x Registration LED
 - 1 x Network Status LED
 - 1 x Power Indicator LED
- External Yealink AC adapter
- AC 100-240V Input and DC 5V/600mA Output
- Base station size: 130mm x 100mm x 25.1mm
- Operating humidity: 10~95%
- Operating temperature: -10~+50°C (+14~122°F)

Package features

Package contents:

- W70B Base Station
- Base Stand
- USB Charger Cradle
- Power Adapter
- Ethernet Cable
- Quick Start Guide



Intermedia has been recognized by J.D. Power for providing "An Outstanding Customer Service Experience" for its Assisted Technical Support. J.D. Power 2021 Certified Assisted Technical Program, developed in conjunction with TSIA. Based on successful completion of an audit and exceeding a customer satisfaction benchmark for assisted support operations. For more information, visit www.jdpower.com or www.tsia.com.

Questions? Contact Us Today.