

Yealink

T44W



GIGABIT, WI-FI, AND BLUETOOTH ENABLED IP PHONE WITH 8 LINES

The Yealink T44W is a feature rich enterprise-level IP phone with extended functionality for excellent communications. Equipped with an extra-large color screen, built-in dual-band 5G Wi-Fi and Bluetooth, and support for up to 8 lines, the T44W is a great choice for all around communication needs.

KEY FEATURES

- 2.8" 320x240 Color LCD Display
- Built-In Dual Band 2.4g/5g Wi-Fi
- Built-In Bluetooth 4.2
- Dual USB Ports
- PoE Support

T44W PHONE PRODUCT SPECIFICATIONS

Audio Features

- HD voice: HD handset, HD speaker
- Hearing aid compatible (HAC) handset
- Acoustic Shield
- Smart Noise Filtering
- Wideband codec: G.722
- Narrowband codec: PCMU (G.711 μ), PCMA (G.711A), G.729,
- DTMF: In-band, Out-of-band(RFC 2833) and SIP INFO
- Full-duplex hands-free speakerphone with AEC
- VAD, CNG, AEC, PLC, AJB, AGC

Phone Features

- 12 VoIP accounts
- One-touch speed dial, redial
- Call forward, call waiting, call transfer, call hold
- Call return, group listening
- Emergency call
- Mute, DND
- Auto answer
- Hoteline
- 5-way conference call
- Ring tone selection/import/delete
- Set date time manually or automatically
- Dial Plan, XML Browser, Action URL/URI
- RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)
- Built-in dual-band Wi-Fi:
 - > Network standard: IEEE802.11a/b/g/n/ac
 - > Transmission rate: Up to 433Mbps (dynamic)
 - > Frequency range: 2.4GHz/5.0GHz
- Built-in Bluetooth 4.2 for:
 - > Bluetooth headsets
 - > Contact synchronization
 - > Bluetooth call
 - > Simultaneous connection of one headset and one mobile phone
- Dual USB ports (2.0 compliant)
 - > USB call recording through USB flash drive
 - > USB headset
 - > Expansion Module EXP43
 - > Wireless Headset Adapter EHS40
 - > USB/Bluetooth connectivity to Yealink CP900 CP700 speakerphone/wireless headset UH38, USB connectivity to Yealink wired headset UH34/UH36/UH37:
 - Basic functions: Answer / end, call mute
 - Enhanced function: audio optimization, redial, call hold, volume synchronization, multiple calls control
- Enhanced DSS key

Directory

- Local phonebook up to 1000 entries
- Blocklist
- XML/LDAP remote phonebook
- Smart dialing
- Phonebook search/import/export
- Call history: dialed/received/missed/forwarded

IP-PBX Features

- Busy Lamp Field (BLF), Bridged Line Appearance
- Anonymous call, anonymous call rejection
- Hot-desking, voice mail
- Call park, call pickup
- Centralized call recording, call recording
- Visual voice mail

Display and Indicator

- 2.8" 320x240-pixel color LCD with backlight
- LED for call and message waiting indication
- Dual-color (red or green) illuminated LEDs for line status information
- Intuitive user interface with icons and soft keys
- Multilingual user interface
- Caller ID with name and number
- Power saving

Feature keys

- 8 line keys with LED
- 8 line keys can be programmed up to 21 paperless DSS keys (3-page view)
- 5 features keys: message, headset, mute, redial, hands-free speakerphone
- 4 context-sensitive "soft" keys
- 6 navigation keys
- 2 volume control keys
- Illuminated mute key
- Illuminated headset key
- Illuminated hands-free speakerphone key

Interface

- Dual-port Gigabit Ethernet
- Power over Ethernet (IEEE 802.3af), Class 3
- 2 x USB port (2.0 compliant)
- 1 x RJ9 (4P4C) handset port
- 1 x RJ9 (4P4C) headset port

Other Physical Features

- Color: Classic Grey
- Stand with 2 adjustable angles
- Wall mountable
- External Yealink AC adapter (optional): AC 100-240 V input and DC 5 V/2 A output
- USB output current: 5 V 500 mA
- Power consumption (PSU): 1.7W - 4.4W
- Power consumption (PoE): 2.0W - 5.2W
- Dimension (W*D*H*T): 224.9 × 206.2 × 174.9 × 52mm
- Operating humidity: 5% to 90%, noncondensing
- Operating temperature: -10 to +45°C (+14 to 113°F)
- Storage temperature: -30 to +70°C (-22 to +158°F)

Management

- Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Auto-provision with PnP
- Broadsoft device management
- Zero-sp-touch TR-069
- Phone lock for personal privacy protection
- Reset to factory, reboot
- Package tracing export, system log

Network and Security

- SIP v1 (RFC2543), v2 (RFC3261)
- Call server redundancy supported
- NAT traversal: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV(RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- SRTP for voice
- Transport Layer Security (TLS 1.3)
- HTTPS certificate manager
- AES encryption for configuration file (AES256)
- Digest authentication: MD5/SHA1/SHA224/-SHA256/SHA384/SHA512
- OpenVPN, IEEE802.1X, L2TP VPN
- IPv6
- LLDP/CDP/DHCP VLAN
- ICE

Package Features

- Package content:
 - > Yealink SIP-T44W IP phone
 - > Handset with handset cord
 - > Ethernet Cable (2m CAT5E UTP Cable)
 - > Stand
 - > Quick Start Guide
 - > Power Adapter (Optional)
 - > Wall Mount Bracket (Optional)
- Qty/CTN: 5 PCS
- N.W/CTN: 5.555kg
- G.W/CTN: 6.148kg
- Giftbox size: 239 × 223 × 115mm
- Carton Meas: 595 × 230 × 248mm

Compliance



Intermedia has been recognized by J.D. Power for providing "An Outstanding Customer Service Experience" for its Assisted Technical Support. J.D. Power 2023 Certified Assisted Technical Program, developed in conjunction with TSIA. Based on successful completion of an audit and exceeding a customer satisfaction benchmark for assisted support operations. For more information, visit www.jdpower.com or www.tsia.com.

Questions? Contact Us Today.